



Washdown Pump Kit

Features & Benefits

- Positive displacement pump
- Can run dry
- Quiet operation
- Demand pump
- Easy connect fittings
- Ignition protected
- Industry standard mount pattern

Typical Applications

- Marine
- General Industrial
- Automotive

PUMP

- Type**
3 or 5 Chamber positive displacement diaphragm pump, self priming, capable of being run dry
- Mode**
Demand
- Liquid Temperature**
140°F (60°C) Max.
- Priming Capabilities**
6 feet (1.8 m) suction lift
- Max Pressure**
70PSI (4.8 bar)

- Inlet/Outlet Ports**
1/2" -14MNPT

- Weight**
8.2 lbs (3.72 kg) -51 series
6.74 lbs (3.06 kg) -33 series

MOTOR

- Duty Cycle**
Intermittent
- Leads**
16 AWG, 4.5' long with 2-Pin connector/Leads
- Voltage**
12v/24v



51F01
fitting 13 mm



51S01
filter 1/2" NPT



51F02
fitting 10 mm



51F03
fitting 13 mm



51H01
UV-protected 25'
Coiled 1/2" O.D. Hose



51SG01



51F05
Straight swivel
adapter fitting,
1/2" NPT(F) X 3/4"
bar (x2)

STANDARD PUMP CONFIGURATIONS

Model	Switch	GPM/LPM	PSI/BAR	Max Draw(A)	Valves	Diaphragm	Ports	Voltage	Wire Connections
SFWP1-050-070-51	Demand	5.0/18.9	70/4.8	18	EPDM	Santoprene	1/2"-14 MPNT	12V	2-Pin/Leads
SFWP2-050-070-51	Demand	5.0/18.9	70/4.8	9	EPDM	Santoprene	1/2"-14 MPNT	24V	2-Pin/Leads
SFWP1-030-070-33	Demand	3.0/11.6	70/4.8	10	EPDM	Santoprene	1/2"-14 MPNT	12V	2-Pin/Leads
SFWP2-030-070-33	Demand	3.0/11.6	70/4.8	5	EPDM	Santoprene	1/2"-14 MPNT	24V	2-Pin/Leads